

Material Safety Data Sheet
May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List)
OPC Drum in DK-18 for DP80F and DP85F

Section I

Manufacturer's Name TOSHIBA TEC CORPORATION	Emergency Telephone Number
Address (Number, Street, City, State, and ZIP Code) Shuwa-Shiba Park Bldg. A, 4th floor 2-4-1, Shihakoen Minato-ku, Tokyo 105, JAPAN	Telephone Number for Information +81-3-3436-6948
	Date Prepared 1-Nov-98
	Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	CAS No.	OSHA PEL	ACGIH TLV	Other Limits	
				Recommended	% (optional)
Coating Layer					< 1
Binder resin	+++	N.A.	N.A.	N.A.	
Photosensitive material	+++	N.A.	N.A.	N.A.	
Pigment	+++	N.A.	N.A.	N.A.	
Substrate					> 99
Aluminum	+++	N.A.	N.A.	N.A.	
+++; Supplier's confidential information					

Section III - Physical/Chemical Characteristics

Boiling Point	N. A.	Flash Point	N. A.
Vapor Pressure (mm Hg.)	N. A.	Melting Point	No data available
Density (g/cm ³)	2.7	pH	N. A.
Explosion Properties	N. A.	Flammability	N. A.
Oxidizing Properties	N. A.	Ignition Temperature (Degrees Centigrade)	N. A.
Solubility in Water	Insoluble	Partition Coefficient, n-octanol/Water	N. A.

Appearance and Odor

Green, solid cylinder and odorless

Section IV - Fire and Explosion Hazard Data

Flash Point (Method used)	N. A.	Flammable Limits	LEL	UEL
			N.A.	N.A.

Extinguishing Media

Water, foam, CO₂ and dry chemicals

Extinguishing Media to Avoid

None

Special Firefighting Procedures

None

Unusual Fire and Explosion Hazards

This materials has no unusual fire or explosion hazards.

Protection of Firefighters

No special equipment is required.

(Reproduce locally)

* N. A. Not Available

OSHA 174, Sept. 1985